



Ruggedness You Can Trust

- High value and amazing total cost of ownership!
- Built to last for extended service life.
- Engineered for minimal maintenance.
- Designed for easy access when maintenance is required.
- A trusted brand made in the USA since 1938.

Bandrite 6000 Features and Technical Data

Dependable Performance

- Industrial-grade durability: Constructed for multi-shift, production-line use, with heavy-gauge frames and industrial electronics designed for uptime.
- Wide Variety of Applications: Ideal for USDA and MIL-SPEC environments—perfect for food, agriculture, military, and many more!
- **High Throughput**: Outstanding seals at fast speeds.
- **Simple and Easy Operation**: Power, speed and temperature controls in one convenient panel.
- Easy to Maintain: Simplified access to sealing bands and heat/cool bars means maintenance and repairs are fast, and without specialized tools.



Feature	Specification
Sealing Speed	Up to 750 in/min (≈62 ft/min)
Seal Width	3/8" or 3/4" flat; optional crimp
Film Capacity	12 mil flat, 6 mil gusset (24 mil total)
Heat Control	Up to 600 ±2 °F
Bandrite Dims	59" x 58.25" x 34"
Weight	450 lbs.
Materials Sealed	Kraft; foils; polypropylene, cellophane, MIL- SPEC material, Poly laminates & polyethylene & More!
Max/Min Height	Max 58.25" Min 19"
Bar Lengths	10" heating, 8" cooling for consistent, high strength seals
Electrical	115 V, 50/60Hz, 1 Phase
Bag Feeding Direction	Right-to-left or left-to-right (at time of order)
Tool-less band swaps	Change sealing bands in minutes—no tools, zero downtime
Neoprene belt-driven	Handles rugged environments
Country of Origin	USA

Bandrite 6000 Accessories

Pressure Rollers

Ensures smooth, consistent seals with a clean, professional look.

Emboss Coder

Imprints date or lot codes directly onto each seal for traceability.

Bag Counter

Tracks and displays accurate counts of sealed bags to streamline production.

Bag Perforator

Allows for easy tear perforations for user-friendly bag opening.

Infeed Assist Guides

Improves safety and efficiency during bag feeding.

Bag Crimpers

Forms unique, high quality seal patterns.

Bag Trimmer

Trims bags to edge of the seal for consistent appearance.

Optional Caster Set

- 360° swivel capability for tight maneuvering in crowded or flexible production layouts.
- Makes repositioning equipment simple for cleaning, maintenance, or process reconfiguration.
- Designed to bolt directly to the frame with included mounting hardware.
- Adds an additional 4 inches to the overall height.



BANDRITE 6000 Stainless Steel Conveyors

Speed & Control

Variable DC speed control up to 750 in/min, synchronized with BANDRITE sealing speeds.

2 feed directions (right-to-left or left-to-right) for seamless line integration.

Durable Construction

Heavy-duty stainless-steel frame for stability and sanitary operation.

Equipped with leveling feet (±2") or lockable casters for mobility and setup flexibility.

Belt Quality

USDA-approved neoprene belt, water-resistant, food-grade, and slip-resistant. Ideal for light to heavy bag loads.

Height & Length Flexibility

Standard belt height is ~30" from floor (adjustable as needed).

Available lengths include 8 ft (9' overall) and 16 ft (17' overall) runs—customizable per line specs.

Power Requirements

Single-phase 115 V, 50/60 Hz AC — compatible with standard US outlets and BANDRITE sealers.



Conveyor Accesories:

Caster Kit

Adds mobility for easy respositioning of equipment (4 inches in height)

· Sealer/Conveyor Caddie

Provides a convenient mounting platform for both sealer and conveyor

Synchronizing Drive

Matches conveyor speed with the Bandrite for seamless operation



For more information

PackRite, LLC 886 FreewayDrive N Columbus, OH 43229 800-248-6868 www.packrite.com Email: packrite@packrite.com